

REAL-TIME IMAGE ENHANCER FOR ANALOG VIDEO

LYYN T38™ is the solution to your visibility problems in subsea, fog, haze, smoke, dust, rain, low-light and many more situations.



[Click to enlarge image](#)

The true power of LYYN T38™ is that the visibility enhancement is done in real-time in a live video stream. And you can also use it on stored material. Use the LYYN™ T38™ to enhance the feed from a live video system, e.g. in a ROV or a surveillance system. Or to enhance a video tape in a camera brought back to office after some fieldwork. Or wherever you need to see more with video.

The LYYN T38™ is easy to use. Connect it in-between the camera and a monitor, tv set or vcr and real-time image enhancer for analog video

LYYN T38™ in sub sea



PDF 0.9MB

LYYN T38™ in security & surveillance



PDF 0.9MB

lyynification™ in real life

Visit the LYYN™ customer showroom for some real life tests! [\[more\]](#)

Testimonials from users [\[more\]](#)

Video samples

you are up and running. With controls for enhancement level and size and position of a rectangular selection of the scene you can always make sure to catch the object on film, and see it.

If you need visibility aid in the field you connect the LYYN T38™ in-between your camera and an external screen. The screen will show enhanced visibility real-time, helping you zooming and focusing on the right object.

The pictures speak for themselves.

In any situation where you need a clear view, you need LYYN T38™.



A clear view under water

Easy to use real-time enhancement processing



LYYN T38™
- easy to use and connect

Model	LYYN T38™
Supported video formats	Analog PAL and NTSC (Time Base Correct, Internal Sync)
Supported audio formats	n/a




11MB

A misty morning on the road - not so misty anymore



36MB

How beautiful is a garden in moon light?



6.7MB

The murky waters of the Baltic Sea are suddenly more agreeable



3.2MB

Find the New Yorkers in the blizzard...

Frame rate	PAL: 25 fps NTSC: 30 fps
Sources	Real-time live video feed Stored material, e.g. from VHS player, video camera, etc
Buffering	1 frame
Delay	PAL: 1/25 second NTSC: 1/30 second
Image settings	lyynification™ level Rectangular selection, size and position
Connectors	BNC analog video, NTSC/PAL auto sensing
Casing	Metal casing. Standalone.
Power	12V DC, 2,5A
Operating conditions	5-50°C (41-122 °F) Humidity 20-80% RH (non-condensing)
Included Accessories	Power supply 12V DC, 12V car plug Video cable, BNC connectors 2 BNC to RCA video connector adaptors
Approvals	CE
Dimensions	54x172x184 (HxWxD in mm)
Weight	925g, excl. power supply



4MB

...or some soldiers in a sand storm in Iraq



0.3MB

In large and in small, even as small as in a microscope, whatever your need is, LYYN™ provides a better view

Get QuickTime

All Clips on the LYYN™ site are in QuickTime MOV format. If you can not view them, please download QuickTime here:

